



Product's Highlights

- 2 Pairs Shielded 22 AWG (7 x 30) Tinned Copper Conductor
- Individually foil shielded 100% coverage

Description

Netway N2PSMC723 was built using 22 gauge (7 x 30) tinned copper conductor for Indoor use. The 2 pairs twisted pair with individually shielded cable contain a separate drain wire for grounding. Widely use in instrumentation applications where optimum noise rejection is required. It provide maximum protection from crosstalk and common mode interference.

Technical Specifications

Description	
Conductor	2 Pairs 22 AWG (7 x 30) Stranded, Tinned Copper
Insulation Material	PP-Polypropylene
Outer Shielded Material Overall	Individually Foil Shield 100% Coverage
Outer Jacket	Polyvinyl Chloride (PVC), Gray Color
Outer Shield Drain Wire AWG	22 AWG (7 x 32) Tinned Copper
Overall Cabling Diameter	4.8mm ± 10%
Pairs Color Code	No1 (Red / Black), No2 (Green / White)
Operating Temperature Range	-30°C To +60°C
Electrical Characteristics	
Impedance	52 Ohm ± 20%
Max Operating Voltage	300V RMS
Max Recommended Current	2.3 Amps per conductor at 25°C

Applications

- Communication, control and instrumentation applications

Ordering Information

Indoor Type 2 Pairs Shielded 22AWG Control Cable, 305 meters per drum

Order Info: NETWAY N2PSMC723

Other Related Product

Indoor Type 1 Pair Shielded 18AWG Control Cable, 305 meters per drum

Order Info: NETWAY N2CSMC760

Indoor Type 1 Pair Shielded 22AWG Control Cable, 305 meters per drum

Order Info: NETWAY N1PSMC761

Indoor Type 2 Pairs Shielded 18AWG Control Cable, 305 meters per drum

Order Info: NETWAY N2PSMC341

Outdoor Type 2 Pairs Shielded 18AWG Control Cable, 305 meters per drum

Order Info: NETWAY N2PSMCX41

Indoor Type 3 Pairs Shielded 22AWG Control Cable, 305 meters per drum

Order Info: NETWAY N3PSMC777